

SOLITEX UM

Brand: ProClima

Product Code: 12739

Weight: 41.89lb

Dimensions: 59.00in x 16.00in x 16.00in

Price: \$622.00



Short Description

SOLITEX UM (59" wide) -- Water Resistant Barrier with 8mm drainage mesh, 38 perms

Description

A 4-layer vapor open waterproof membrane with 3d mesh for integrated venting. Monolithic TEEE actively vapor open protection for metal roofs and vented rain screen facades. With integrated butyl adhesive strips, SOLITEX UM provides superior weather protection even at low pitches (3:12..

Roll Dimensions: 404.87' (124.75m) x 82' (25 m) [404 sf] 59" x 82' (1.50 x

Advantages

- Provides superior weather protection and protection against back sided condensation issues on metal roofs
- No leaks because of tenting effect or wood tannins, unlike microporous membranes
- Protects against noise transmission on metal roofs because of 3d mesh support
- 10 year comprehensive [ProClima warranty](#)
- Integrated butyl adhesive strips, for excellent weather protection of lower sloped roofs
- Suitable as temporary roofunderlayment and wall protection when taped with TESCON VANA on horizontal seams

Properties

- Material: vapor open monolithic TEEE membrane with 0.3" (8 mm) 3D drainage mesh
- Air permeance: 0.00004 cfm/ft²
- Perm Rating: 38 perms (Sd-value 0.05 m) for enhanced outward drying potential
- Very watertight, resists 33' ft of water column

- UV/weather Resistance: 3 months of exposure