

# SOLITEX Mento Plus-- Water Resistant Barrier, 38 perms



**Brand:** ProClima  
**Product Code:** 12905  
**Weight:** 28.66lb  
**Dimensions:** 61.00in x 8.00in x 8.00in

**Price: \$371.75**

## Short Description

SOLITEX Mento Plus-- Water Resistant Barrier, 38 perms

## Description

SOLITEX Mento Plus--

Reinforced, airtight, 4-ply, vapor open, weather resistive barrier and roof underlayment. This highly durable membrane is designed to replacing sheathing, and can be used as netting for dense-packing insulation. Great protection for vented facades and roofs under construction, excellent durability for prefab panels

## Advantages

- Actively vapor open, monolithic layer of TEEE film is also extremely waterproof and airtight
- Can be used without exterior sheathing in vented rainscreens and roofs
- Very robust, used as temporary roofing and wall protection when taped with TESCON VANA
- No leaks because of tenting effect or wood tannins, unlike microporous membranes – [The MENTO difference](#)
- 10 year comprehensive [Pro-Clima warranty](#)

**Roll area: 807.53' (7504<sup>2</sup>) (1.50 x 50 m)**

## Properties:

- Material: non-porous TEEE functional membrane

- Durability: Covered by two PP protection fleeces and includes reinforcement grid
- Water column: Resist over 8' (2.5 m) of water column to ensure protection from the elements
- Perm Rating: 38 perms (Sd-value 0.05 m) for enhanced outward drying potential
- Fire rating: Class A material per ASTM E84 test (0 FS, 85 SDI)
- UV/weather Resistance: Temporary roofing/weatherproofing of façade and roof for up to 4 months - certified by ZVDH (German roofing assoc)
- Artificial aging: Pass long-term testing per DIN EN 1297 / DIN EN 1296